

AIR PREPARATION UNITS FILTER REGULATOR COMBINATION series

Kushako

Filter Regulator Combination details:

Features:


- Modular type for easy and fast maintenance.
- Suitable for wall mounting.
- Filter Bronze / Plastic sintered element
 - Separator and shield for efficient moisture separation.
 - Press type Manual drain for easy operation .
- Regulator Diaphragm operated, relieving type .
 - Pressure compensated by balanced poppet .
 - Non raising 'Press to lock' adjusting knob for locking at
 - any set pressure.

Precautions:

- \bullet Note the direction of flow before installation & connect pipe accordingly.
- Nipples of taper threads to be used with teflon tape. Ensure teflon tape does not enter the unitduring tightening.
- Flush piping for dirt, dust, rust & other foreign particles.
- Install in clean atmosphere.

Technical Specifications:

Model	FRC-2016-14-FM-SA-MK
Medium	Compressed Filtered air
Port Size	G1/4, 3/8, 1/2 BSP / NPT (F)
Pressure gauge port size	G1/8, 1/4 BSP (F)
Flow rate (Ltr / Min)	3000
Maximum supply pr (bar)	12
Regulating pr range (bar)	0 - 2, 0 - 4, 0 - 7, 0 - 10 (Standard)
Ambient / Medium temp	-5° to 60° C
Filteration (µm)	1, 5, 25 & 40 (standard), 50 , 100
Bowl capacity (ml)	50
Bowl material	Metal
Installation	Vertical
Materials of construction	Aluminium, Brass, SS, Nitrile
Optional accessories	Clamp, Modular mounting kit, Pr gauge
Weight (Kg)	1.2kg







Manufactured by:

Kushako India

Office: 490, Narayan Peth, Opp. Pune Marathi Granthalaya, Pune - 411030. (Maharashtra), Website: www.kushakoindia.com

Works: Sr.No. 25/1A, Village Nanded, Sinhgad Road, Tal - Haveli, Dist. Pune -411041

Tel. No: 901169077 / 7620674777

E-mail: kushako.india@gmail.com / kushakoindia1992@gmail.com



<u>Kushako</u>