

# AIR PREPARATION UNITS FRCLM MODULAR series



### Filter Regulator Combination details:


#### Features:

- Modular type for easy and fast maintenance.
- · Suitable for wall mounting.
- Filter Bronze / Plastic sintered element
  - Separator and shield for efficient moisture separation.
  - Press type Manual drain for easy operation.
- Regulator Diaphragm operated, relieving type .
  - Pressure compensated by balanced poppet .
  - Non raising 'Press to lock' adjusting knob for locking at
  - any set pressure.
- Lubricator Fog / Mist type Lubricator
  - Fine adjustment of Lubrication
  - Lubrication Proportional flow
- Good flow and regulating characteristics.


#### Precautions:

- · Note the direction of flow before installation and connect piping accordingly.
- · Install in clean atmosphere.
- Polycarbonate bowls may get damaged and possibly fail if exposed to synthetic oils, thinner, solvents tricholoethylene, Kerosene or other hydrocarbons.
  Technical specification

Model	FRCLM-2016-M
Medium	Compressed air - Filtered
Port Size	1/2 BSP (F)
Pressure gauge port size	1/8 BSP (F)
Flow rate ( Ltr / Min )	2800
Maximum supply pressure (bar)	12
Regulating pressure range (bar)	0.2-2, 0.2-4,0.5-7, (0.5 - 10) (Standard)
Ambient / Medium temperature	5° - 60° C
Filteration ( µm )	1, 5, 25 & 40 Micron ,100 option
Minimum operating flow , Ltr / Min	45
Bowl capacity Filter ( ml )	152
Recommended Oil	ISO VG 32
Bowl material	Metal
Installation	Vertical
Materials of construction	Aluminium, Brass, Steel, SS, NTR/PC
Optional accessories	Clamp, Modular mounting kit, Gauge
Weight (kg)	1.650









Manufactured by:

## Kushako India

Office: 490, Narayan Peth, Opp. Pune Marathi Granthalaya, Pune - 411030. (Maharashtra), Website: www.kushakoindia.com

Works: Sr.No. 25/1A, Village Nanded, Sinhgad Road, Tal - Haveli, Dist. Pune -411041

Tel. No: 901169077 / 7620674777

E-mail: kushako.india@gmail.com / kushakoindia1992@gmail.com

