


AIR PREPARATION UNITS FRCLM MODULAR series



Filter Regulator Combination details:

Features:

- Modular type for easy and fast maintenance.
- Suitable for wall mounting.
- Bronze / Plastic sintered element Filter
 - Separator and shield for efficient moisture separation.
 - Press type Manual drain for easy operation .
- Regulator Diaphragm operated, relieving type .
 - Pressure compensated by balanced poppet.
 - Non raising 'Press to lock' adjusting knob for locking at
 - any set pressure.
- Lubricator Fog / Mist type Lubricator
 - Fine adjustment of Lubrication
 - Lubrication Proportional flow
- · Good flow and regulating characteristics.




- Note the direction of flow before installation and connect piping accordingly.
- Install in clean atmosphere.
- Polycarbonate bowls may get damaged and possibly fail if exposed to synthetic oils, thinner, solvents tricholoethylene, Kerosene or other hydrocarbons.

Technical specification

Model	FRCLM-2012 (Eco)
Medium	Compressed air - Filtered
Port Size	1/4 (BSP) (F)
Pressure gauge port size	1/8 (BSP) (F)
Flow rate (Ltr / Min)	500
Maximum supply pressure (bar)	10
Regulating pressure range (bar)	0.2-2, 0.2-4,0.5-7, (0.5 - 10) (Standard)
Ambient / Medium temperature	5° - 60° C
Filteration (µm)	1, 5, 25 & 40 Micron ,100 option
Minimum operating flow,Ltr / Min	12
Bowl capacity Filter (ml)	40
Recommended Oil	ISO VG 32
Bowl material	Polycarbonate
Installation	Vertical
Materials of construction	Aluminium, Brass, Steel, SS, NTR/PC
Optional accessories	Clamp, Modular mounting kit, Gauge
Weight (kg)	0.400









Manufactured by:

Kushako India

Office: 490, Narayan Peth, Opp. Pune Marathi Granthalaya, Pune - 411030. (Maharashtra), Website: www.kushakoindia.com

Works: Sr.No. 25/1A, Village Nanded, Sinhgad Road, Tal - Haveli, Dist. Pune -411041

Tel. No: 901169077 / 7620674777

E-mail: kushako.india@gmail.com/kushakoindia1992@gmail.com

