## AIR PREPARATION UNITS AIR FILTER series

### Air Filter details :

#### Features :

- Suitable for modular mountings.
- •Press type manual drain for easy operation.
- •Bronze / Plastic sintered element .
- Separator & shield for efficient moisture separation.


#### **Precautions** :

- •Note the direction of flow before installation & connect pipe accordingly.
- ${\scriptstyle \bullet} Nipples$  of taper threads to be used with teflon tape. Ensure teflon tape does not
- enter the unit during tightening. Nipples of straight threads to be used with sealing washer.
- •Flush piping for dirt, dust, rust & other foreign particles.
- Install in clean atmosphere.
- Polycarbonate bowl may get damaged & possibly fail if exposed to synthetic oils, thinner, solvents, trochloroethylene, kerosene or other aromatic hydrocarbons.

#### **Technical Specifications**:

Model	AF-2012(Eco)
Medium	Compressed air
Port Size	G1/4 BSP (F)
Bowl capacity (ml)	15
Flow rate ( Ltr / Min )	800
Maximum supply pressure (bar)	10
Filteration (µm)	1, 5, 25, 40 ( standard ) , 50,100
Bowl material	Polycarbonate
Ambient / Medium temperature	5° - 60° C
Installation	Vertical (As in the picture)
Materials of construction	Aluminium, Brass, Steel, SS, Nitrile
Optional accessories	Clamp, Modular mounting kit, Pr gauge
Weight (Kg)	0.103

• Supply pressure 6 bar , pressure drop p= 0.3 bar (for standard models).





#### Manufactured by : Kushako India Office : 490. Naravan Peth. Op

Kushako

Office : 490, Narayan Peth, Opp. Pune Marathi Granthalaya, Pune - 411030. (Maharashtra), Website : www.kushakoindia.com Works : Sr.No. 25/1A, Village Nanded, Sinhgad Road, Tal - Haveli, Dist. Pune -411041 Tel. No : 901169077 / 7620674777 E-mail : kushako.india@gmail.com / kushakoindia1992@gmail.com



# <u>Kushako</u>